



TYSONIC SPEAKER FLEX
PRODUCT SPECIFICATION

1.PRODUCT CODE LMC02/3.3

2. DESCRIPTION 2 Core 41/32 (3.3mm sq nom.) V75 P.V.C insulated.
HBZRH-80FZW Low smoke, Low Halogen P.V.C. sheathed .
Tysonic Speaker Flex.
Oxygen free copper . RoHS compliant .

3. CONSTRUCTION

3.1 CONDUCTOR : 41 strands of 0.32 mm Annealed Copper to
AS/NZS1125 drawn from Class 102 copper to AS/NZS1574.
Max. D.C. resistance at 20C : 5.6 ohms / km

3.2 INSULATION : Coloured V75 PVC to AS/NZS3808
Nominal Diameter : 2.5 mm
Nom. Wall Thickness: 0.60 mm

3.3 LAY UP 2 Cores.
1. Red plus 2. Black

3.4 SHEATH Coloured P.V.C. type HBZRH-80FZW
Nominal Diameter : 8.4 mm
Nom. Wall Thickness : 1.0 mm

3.4 IDENTIFICATION

Printed at max 1000mm spacings

Cable to be meter marked, i.e every 1 meter

TYCAB NZ Y.O.M. – 3.3mm² 12AWG 2 CORE 100V LINE SPEAKER CABLE M/M