



**TYSONIC SPEAKER FLEX**  
**PRODUCT SPECIFICATION**

**1.PRODUCT CODE** LMC04/2.1

**2. DESCRIPTION** 4 Core 105/.16 (2.1mm sq nom.) V75 P.V.C insulated.  
HBZRH-80FZW Low smoke, Low Halogen P.V.C. sheathed .  
Tysonic Speaker Flex.  
Oxygen free copper . RoHS compliant .

**3. CONSTRUCTION**

**3.1 CONDUCTOR :** 105 strands of 0.16 mm Annealed Copper to AS/NZS1125 drawn from Class 102 copper to AS/NZS1574.  
Max. D.C. resistance at 20C : 8.6 ohms / km

**3.2 INSULATION :** Coloured V75 PVC to AS/NZS3808  
Nominal Diameter : 2.65 mm  
Nom. Wall Thickness: 0.60 mm

**3.3 LAY UP** 4 Cores.  
1. Red 2. Black 3. White 4. Green

**3.4 SHEATH** Coloured P.V.C. type HBZRH-80FZW  
Nominal Diameter : 8.5 mm  
Nom. Wall Thickness : 1.0 mm

**3.4 IDENTIFICATION**

Printed at max 1000mm spacings

Cable to be meter marked, i.e every 1 meter

TYCAB NZ Y.O.M. – 2.1mm<sup>2</sup> 14AWG 4 CORE 100V LINE SPEAKER CABLE M/M