




TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833
A.C.N. 100 305 833
269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)
DANDENONG STH VICTORIA 3164
TELEPHONE 03 (Int. 613) 8791 0300
FAX - ADMIN 03 (Int. 613) 9794 0031
CUSTOMER SERVICE
PHONE 03 (Int. 613) 8791 0333
FAX 03 (Int. 613) 9791 8732
www.tycab.com.au

PRODUCT SPECIFICATION



1. PRODUCT CODE **ABC145503**

2. DESCRIPTION **399/.32 (32.07mmsq – 2 B&S)**
Plain Copper Automotive Battery cable.
60Volt V90 PVC. Not for Mains Connection.
Oxygen Free Copper. RoHS compliant PVC.

3. CONSTRUCTION

3.1 CONDUCTOR: **399** strands of 0.32mm Plain Annealed Copper to AS/NZS1125 drawn from Class 102 copper to AS/NZS1574.

Max. D.C. resistance at 20C: 0.6 ohms / km

TYPICAL conductor diameter: 7.55 mm

3.2 INSULATION: Coloured P.V.C. type V90 to AS/NZS 3808
Nominal Diameter: 11.0 mm
Nominal Wall Thickness: 1.7 mm

4. REFERENCE STANDARDS

4.1 AS/NZS3808 **PVC** compound type.

4.2 AS/NZS1125 Conductor Tolerances

4.3 AS/NZS1574 Copper Type

4.4 SAE J1127 Minimum cross-section conductor area and Minimum Wall Thickness

AUSTRALIAN MADE CABLES LEADING THE WAY