




## TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833  
A.C.N. 100 305 833  
269 FRANKSTON-DANDENONG ROAD  
(LOCKED BAG 1413)  
DANDENONG STH VICTORIA 3164  
TELEPHONE 03 (Int. 613) 8791 0300  
FAX - ADMIN 03 (Int. 613) 9794 0031  
CUSTOMER SERVICE  
PHONE 03 (Int. 613) 8791 0333  
FAX 03 (Int. 613) 9791 8732  
[www.tycab.com.au](http://www.tycab.com.au)

### PRODUCT SPECIFICATION



**1. PRODUCT CODE**      **ABC1492032**

**2. DESCRIPTION**      **492/0.32 (39.55 mmsq – 1 B&S)**  
**Plain Copper Wire Automotive Battery cable.**  
**60Volt V90 PVC. Not for Mains Connection.**  
**Oxygen Free Copper. RoHS compliant PVC.**

#### 3. CONSTRUCTION

**3.1 CONDUCTOR:**      **492 strands of 0.32 mm Plain Annealed Copper to AS/NZS1125 drawn from Class 102 copper to AS/NZS1574.**

Max. D.C. resistance at 20C:      0.6 ohms / km

TYPICAL conductor diameter:      8.35 mm

**3.2 INSULATION:**      Coloured P.V.C. type V90 to AS/NZS3808  
Nominal Diameter:      12.1 mm  
Nominal Wall Thickness:      1.7 mm

#### 4. REFERENCE STANDARDS

**4.1 AS/NZS3808**      **PVC compound type.**

**4.2 AS/NZS1125**      **Conductor Tolerances**

**4.3 AS/NZS1574**      **Copper Type**

**4.4 SAE J1127**      **Minimum cross-section conductor area and Minimum Wall Thickness**

**AUSTRALIAN MADE CABLES LEADING THE WAY**