




TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833
A.C.N. 100 305 833
269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)
DANDENONG STH VICTORIA 3164
TELEPHONE 03 (Int. 613) 8791 0300
FAX - ADMIN 03 (Int. 613) 9794 0031
CUSTOMER SERVICE
PHONE 03 (Int. 613) 8791 0333
FAX 03 (Int. 613) 9791 8732
www.tycab.com.au

PRODUCT SPECIFICATION



- 1. PRODUCT CODE** **ABC191003**
- 2. DESCRIPTION** **798/0.32 (64.15 mmsq – 00 B&S)**
Plain Copper Wire Automotive Battery cable.
60Volt V90 PVC. Not for Mains Connection.
Oxygen Free Copper. RoHS compliant PVC.
- 3. CONSTRUCTION**
- 3.1 CONDUCTOR:** **798** strands of 0.32 mm Plain Annealed Copper to AS/NZS1125 drawn from Class 102 copper to AS/NZS1574.
- Max. D.C. resistance at 20C: 0.3 ohms / km
- TYPICAL conductor diameter: 10.65 mm
- 3.2 INSULATION:** Coloured P.V.C. type V90 to AS/NZS3808
- Nominal Diameter: 14.5 mm
- Nominal Wall Thickness: 1.7 mm
- 4. REFERENCE STANDARDS**
- 4.1 AS/NZS3808** **PVC** compound type.
- 4.2 AS/NZS1125** Conductor Tolerances
- 4.3 AS/NZS1574** Copper Type
- 4.4 SAE J1127** Minimum cross-section conductor area and Minimum Wall Thickness

AUSTRALIAN MADE CABLES LEADING THE WAY