



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833
A.C.N. 100 305 833
269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)
DANDENONG STH VICTORIA 3164
TELEPHONE 03 (Int. 613) 8791 0300
FAX - ADMIN 03 (Int. 613) 9794 0031
CUSTOMER SERVICE
PHONE 03 (Int. 613) 8791 0333
FAX 03 (Int. 613) 9791 8732
www.tycab.com.au

PRODUCT SPECIFICATION

1. PRODUCT CODE AFC21603

2. DESCRIPTION 2 Core Parallel Webbed (Figure 8) 14/0.32 (1.13 mm sq). P.A.C.W.
V90 P.V.C insulated.
Extra Low Voltage Automotive cable. Not for mains outlet connection.
50V A.C. 120 D.C. to AS/NZS 3000
Oxygen Free copper. RoHS Compliant PVC.

3. CONSTRUCTION

3.1 CONDUCTOR: 14 strands of 0.32mm Plain Annealed Copper to AS/NZS 1125
drawn from Class 102 copper to AS/NZS 1574.

Max. D.C. resistance at 20C: 16.5 ohms / km

3.2 INSULATION: Coloured V90 P.V.C. to AS/NZS 3808.
Parallel Webbed (Figure 8) construction

Nominal Diameter: 2.6 x 5.9 mm
Nominal Wall Thickness: 0.6 mm

Polarity identification by coloured stripe.