



## **TYCAB AUSTRALIA PTY LTD**

A.B.N. 43 100 305 833

A.C.N. 100 305 833

269 FRANKSTON-DANDENONG ROAD

(LOCKED BAG 1413)

DANDENONG STH VICTORIA 3164

TELEPHONE 03 (Int. 613) 8791 0300

FAX - ADMIN 03 (Int. 613) 9794 0031

CUSTOMER SERVICE

PHONE 03 (Int. 613) 8791 0333

FAX 03 (Int. 613) 9791 8732

[www.tycab.com.au](http://www.tycab.com.au)

### **PRODUCT SPECIFICATION**

- 1.PRODUCT CODE**     **ATC51603**
- 2. DESCRIPTION**     5 Core 14/32 (1.13sqmm) .P.C.W. V90 PVC insulated.  
5V90 PVC sheathed trailer cable.  
60 Volt . Not for Mains connection.
- 3. CONSTRUCTION**
- 3.1 CONDUCTOR :**     14 strands of 0.32 mm Annealed Copper to  
AS1125 drawn from Class 102 copper to AS1574.  
Max. D.C. resistance at 20C : 16.5 ohms / klm
- 3.2 INSULATION :**    Coloured V90 PVC to AS3808.  
Nominal Diameter : 2.2 mm  
Nom. Wall Thickness: 0.4 mm
- 3.3 LAY UP**            5 Cores laid up .  
1. Brown 2. Red 3. Green 4. White 5. Yellow
- 3.4 SHEATH**            Coloured P.V.C. type 5V90 to AS3808.  
Nominal Diameter : 7.1 mm  
Nom. Wall Thickness : 0.6 mm

#### **TYPICAL ROPY TRAILER CABLE FINISH**