



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833

A.C.N. 100 305 833

269 FRANKSTON-DANDENONG ROAD

(LOCKED BAG 1413)

DANDENONG STH VICTORIA 3164

TELEPHONE 03 (Int. 613) 8791 0300

FAX - ADMIN 03 (Int. 613) 9794 0031

CUSTOMER SERVICE

PHONE 03 (Int. 613) 8791 0333

FAX 03 (Int. 613) 9791 8732

www.tycab.com.au

PRODUCT SPECIFICATION

- 1.PRODUCT CODE** ATC57032
- 2. DESCRIPTION** 5 Core 7/32 (0.56sqmm) .P.C.W. V90 PVC insulated.
5V90 P.V.C. sheathed trailer cable.
Extra Low Voltage . Not for Mains GPO connection.
- 3. CONSTRUCTION**
- 3.1 CONDUCTOR :** 7 strands of 0.32mm Annealed Copper to
AS1125 drawn from Class 102 copper to
AS1574. Max. D.C. resistance at 20C : 33.0 ohms / km
- 3.2 INSULATION :** Coloured V90 PVC to AS3808.
Nominal Diameter : 1.8 mm
Nom. Wall Thickness: 0.4 mm
- 3.3 LAY UP** 5 Cores twisted - left hand lay ..
1. Red 2. Brown 3. Yellow
4. Green 5. White
- 3.4 SHEATH** Coloured P.V.C. type 5V90 to AS3808.
Nominal Diameter : 6.0 mm
Nom. Wall Thickness : 0.6 mm

TYPICAL ROPY TRAILER FINISH