



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833

A.C.N. 100 305 833

269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)

DANDENONG STH VICTORIA 3164

TELEPHONE 03 (Int. 613) 8791 0300

FAX - ADMIN 03 (Int. 613) 9794 0031

CUSTOMER SERVICE

PHONE 03 (Int. 613) 8791 0333

FAX 03 (Int. 613) 9791 8732

www.tycab.com.au

PRODUCT SPECIFICATION

- 1.PRODUCT CODE** **ATC71603**
- 2. DESCRIPTION** 7 Core 14/.32 (1.13sqmm) .P.C.W. V90 PVC insulated.
5V90 pvc sheathed trailer cable.
Extra Low Voltage . Not for Mains connection.
Oxygen free copper . RoHS compliant PVC .
- 3. CONSTRUCTION**
- 3.1 CONDUCTOR :** 14 strands of 0.32 mm Annealed Copper to
AS1125 drawn from Class 102 copper to AS1574.
Max. D.C. resistance at 20C : 16.5 ohms / km
- 3.2 INSULATION :** Coloured V90 PVC to AS3808.
Nominal Diameter : 2.2 mm Nom. Wall Thickness: 0.4 mm
- 3.3 LAY UP** 7 Cores laid up .
1. Brown 2. Red 3. Green 4. White 5. Yellow
6.Black 7. Blue
- 3.4 SHEATH** Coloured P.V.C. type 5V90 to AS3808.
Nominal Diameter : 7.8 mm Nom. Wall Thickness : 0.6 mm

TYPICAL ROPY TRAILER CABLE FINISH