



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833

A.C.N. 100 305 833

269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)

DANDENONG STH VICTORIA 3164

TELEPHONE 03 (Int. 613) 8791 0300

FAX - ADMIN 03 (Int. 613) 9794 0031

CUSTOMER SERVICE

PHONE 03 (Int. 613) 8791 0333

FAX 03 (Int. 613) 9791 8732

www.tycab.com.au

PRODUCT SPECIFICATION

1.PRODUCT CODE ATC72603

2. DESCRIPTION 7 Core 23/.32 (1.85sqmm) .P.C.W. V90 PVC insulated.
5V90 pvc sheathed AUTOMOTIVE trailer cable.
60 volt . Not for Mains connection.

3. CONSTRUCTION

3.1 CONDUCTOR : 23 strands of 0.32mm Annealed Copper to
AS1125 drawn from Class 102 copper to
AS1574.
Max. D.C. resistance at 20C : 10.3 ohms / klm

3.2 INSULATION : Coloured V90 PVC to AS3808.
Nominal Diameter : 2.6 mm
Nom. Wall Thickness: 0.4 mm

3.3 LAY UP 7 Cores laid up .
1. Brown 2. Red 3. Green 4. White 5. Yellow
6.Black 7. Blue

3.4 SHEATH Coloured P.V.C. type 5V90 to AS3808.
Nominal Diameter : 8.9 mm
Nom. Wall Thickness : 0.6 mm

TYPICAL ROPY TRAILER CABLE FINISH