



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833

A.C.N. 100 305 833

269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)

DANDENONG STH VICTORIA 3164

TELEPHONE 03 (Int. 613) 8791 0300

FAX - ADMIN 03 (Int. 613) 9794 0031

CUSTOMER SERVICE

PHONE 03 (Int. 613) 8791 0333

FAX 03 (Int. 613) 9791 8732

www.tycab.com.au

PRODUCT SPECIFICATION

1. PRODUCT CODE: AWC2399032

2. DESCRIPTION: 2 Core Flat Twin Sheathed 399/.32 (2 B&S). P.A.C.W.
V90 insulated & sheathed. AUTOMOTIVE CABLE
Extra Low Voltage. Not for Mains GPO Connection.

3. CONSTRUCTION

3.1 CONDUCTOR: 399 strands of 0.32 mm nom. Plain Annealed Copper to
AS/NZS1125 drawn from Class 110A copper to AS/NZS1574.

Max. D.C. resistance at 20C: 0.6 ohms / km

3.2 INSULATION: Coloured V90 P.V.C. to AS/NZS3808.

Nominal Diameter: 11.0 mm

Nominal Wall Thickness: 1.7 mm

3.3 CORE COLOURS: 1. Red
2. Black
Laid parallel

3.4 SHEATH: Coloured 5V90 to AS/NZS3808
Flat configuration

Nominal Dimensions: 13.1 x 24 mm

Nominal Wall Thickness: 0.96 mm

AUSTRALIAN MADE CABLES LEADING THE WAY