



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833
A.C.N. 100 305 833
269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)
DANDENONG STH VICTORIA 3164
TELEPHONE 03 (Int. 613) 8791 0300
FAX - ADMIN 03 (Int. 613) 9794 0031
CUSTOMER SERVICE
PHONE 03 (Int. 613) 8791 0333
FAX 03 (Int. 613) 9791 8732
www.tycab.com.au

PRODUCT SPECIFICATION



- 1. PRODUCT CODE:** AWC26503
- 2. DESCRIPTION** 2 Core Flat Twin Sheathed 57/.32 (4.58mmsq). P.A.C.W.
V90 Insulated & 5V90 Sheathed Automotive.
Extra Low Voltage, Not for Mains Connection.
- 3. CONSTRUCTION**
- 3.1 CONDUCTOR:** 57 strands of 0.32mm Plain Annealed Copper to AS/NZS 1125
drawn from Class 110A copper to AS/NZS 1574.
Max. D.C. resistance at 20C: 4.1 ohms / km
- 3.2 INSULATION:** Coloured V90 P.V.C. to AS/NZS 3808.
Nominal Diameter: 4.0 mm
Nominal Wall Thickness: 0.6 mm
- 3.3 CORE COLOURS:** 1. Red
2. Black
Laid parallel
- 3.4 SHEATH:** Coloured 5V90 to AS/NZS 3808
Flat configuration
Nominal Dimensions: 5.65 x 9.60 mm
Nominal Wall Thickness: 0.8 mm

AUSTRALIAN MADE CABLES LEADING THE WAY