



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833

A.C.N. 100 305 833

269 FRANKSTON-DANDENONG ROAD

(LOCKED BAG 1413)

DANDENONG STH VICTORIA 3164

TELEPHONE 03 (Int. 613) 8791 0300

FAX - ADMIN 03 (Int. 613) 9794 0031

CUSTOMER SERVICE

PHONE 03 (Int. 613) 8791 0333

FAX 03 (Int. 613) 9791 8732

www.tycab.com.au

PRODUCT SPECIFICATION

1. PRODUCT CODE AWM719019

2. DESCRIPTION 7 Core 19/.19 (0.54sqmm) .P.C.W. V90 PVC insulated.
5V90 P.V.C. sheathed
FLAT trailer cable.
60 Volts DC or 25 Volts AC . Not for Mains GPO connection.

3. CONSTRUCTION

3.1 CONDUCTOR : 19 strands of 0.19mm Annealed Copper to
AS1125 drawn from Class 110A copper to
AS1574. Max. D.C. resistance at 20C : 35.0 ohms / km

3.2 INSULATION : Coloured V90 PVC to AS3808.
Nominal Diameter : 2.2 mm
Nom. Wall Thickness: 0.6 mm

3.3 LAY UP 7 Cores in sequence :
1. Brown 2. Red 3. Lt. Blue 4. Green 5. White 6. Black
7. Yellow

3.4 SHEATH **FLAT**
Coloured P.V.C. type 5V90 to AS3808.
Nominal Diameter : 4.5 X 17.6 mm
Nom. Wall Thickness : 1.0 mm