



## PRODUCT SPECIFICATION

**1. PRODUCT CODE** BELS37067

**2. DESCRIPTION** 2 Core Flat Twin and Earth 7/67 (2.5 mm sq nom.). P.A.C.W.  
HFI-90-TP insulated and HFS-90-TP sheathed. Low Smoke Zero Halogen.  
Building Cable 450/750 Volt to AS5000.2

### 3. CONSTRUCTION

**3.1 CONDUCTOR :** 7 strands of 0.67 mm Plain Annealed Copper to AS1125 drawn from Class 110A copper to AS1574.  
Max. D.C. resistance at 20C : 7.4 ohms / km

**3.2 INSULATION :** Coloured HFI-90-TP. to AS3808 .

Nominal Diameter : 3.4mm  
Nom. Wall Thickness: 0.7mm

#### 3.3 CORE COLOURS

1. Red 2. Green / Yellow 3 . Black  
Laid parallel.

**3.4 SHEATH :** Coloured HFS-90-TP to AS3808  
Flat configuration

Nominal Dimensions : 5.5 x 12.2 mm  
Nom. Wall Thickness : 1.0 mm

### IDENTIFICATION

Printed on the sheath

TYCAB 2008 ELECTRIC CABLE HFI-90-TP 450/750V \* 2.5MMSQ T&E