



PRODUCT SPECIFICATION

1. PRODUCT CODE BWT2704

2. DESCRIPTION 2 Core Flat 7/4 (1.0 mm sq nom.). Tinned Copper Wire,
V90 PVC Insulated & 5V90 Sheathed with Tyrip Tear initiator.
FIRE ALARM CABLE, generally 450/750volt.
Oxygen Free copper. RoHS compliant.

3. CONSTRUCTION

3.1 CONDUCTOR: 7 strands of 0.4 mm Tinned Annealed Copper to
AS1125 drawn from Class 102 copper to AS1574.
Max. D.C. resistance at 20C : 21.6 ohms / km

3.2 INSULATION: Coloured V90 P.V.C. to AS3808.
Nominal Diameter : 2.4 mm
Nominal Wall Thickness : 0.6 mm

3.3 CORE COLOURS: 1. Red
2. Black
Laid parallel.

3.4 SHEATH: Coloured 5V90 PVC to AS3808
Flat configuration
Nominal Dimensions : 4.2 x 6.7 mm
Nominal Wall Thickness : 0.9 mm

3.5 IDENTIFICATION: Printed on sheath at Max. 500mm spacings

TYCAB 2011 V90 ELECTRIC CABLE 450/750Volt BWT2704