



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833

A.C.N. 100 305 833

269 FRANKSTON-DANDENONG ROAD

(LOCKED BAG 1413)

DANDENONG STH VICTORIA 3164

TELEPHONE 03 (Int. 613) 8791 0300

FAX - ADMIN 03 (Int. 613) 9794 0031

CUSTOMER SERVICE

PHONE 03 (Int. 613) 8791 0333

FAX 03 (Int. 613) 9791 8732

www.tycab.com.au

PRODUCT SPECIFICATION

1.PRODUCT CODE DPF12702

2. DESCRIPTION 6 Pair 7/2 (0.2 mm sq) 24AWG .T.A.C.W. Polypropylene insulated. Aluminium Laminate tape screened.PVC sheathed.Data cable.

3. CONSTRUCTION

3.1 CONDUCTOR : 7 strands of 0.2 mm Tinned Annealed Copper to AS1125 drawn from Class 110A copper to AS1574. Max. D.C. resistance at 20C : 89 ohms / klm

3.2 INSULATION : Coloured Data Grade Polypropylene.
Nominal Diameter : 1.2 mm
Nom. Wall Thickness: 0.3 mm

3.3 LAY UP 6 Pairs laid up.

Pair1. Blue + White/Blue	Pair 2. Orange + White/Orange
Pair3 Green + White/Green	Pair4 Brown + White/Brown
Pair5 Grey + White/Grey	Pair6 Blue + Red/Blue

3.4 SCREEN

Aluminium / Polyester Laminate tape in constant contact with a 7/2 TACW drain wire.

3.4 SHEATH

Coloured 4V75 PVC to AS3808 .
Nominal Diameter : 7.8 mm Nom. Wall Thickness : 0.76 mm

3.5 TYPICAL ELECTRICAL

TYPICAL CAPACITANCE 55 pF/m

3.6 PRINTING

At nominally 1M spacings printed on sheath :
“TYCAB AUSTRALIA MULTIPAIR DATA DPF12702 CCL A93/CA/0111”

AUSTRALIAN MADE CABLES LEADING THE WAY