

**TYCAB AUSTRALIA PTY LTD**

A.B.N. 43 100 305 833

A.C.N. 100 305 833

269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)

DANDENONG STH VICTORIA 3164

TELEPHONE 03 (Int. 613) 8791 0300

FAX - ADMIN 03 (Int. 613) 9794 0031

CUSTOMER SERVICE

PHONE 03 (Int. 613) 8791 0333

FAX 03 (Int. 613) 9791 8732

www.tycab.com.au**PRODUCT SPECIFICATION****1. PRODUCT CODE** DPF2702**2. DESCRIPTION** 1 Pair 7/2 (0.2 mm sq) 24AWG. T.A.C.W.
Polypropylene insulated.
Aluminium Laminate tape screened.
PVC sheathed. Data cable.
Extra Low Voltage. Not for mains outlet connection.**3. CONSTRUCTION****3.1 CONDUCTOR:** 7 strands of 0.2mm nom. Tinned Annealed Copper to AS/NZS1125
drawn from Class 110A copper to AS/NZS1574.

Max. D.C. resistance at 20C: 89 ohms / km

3.2 INSULATION: Coloured Data Grade Polypropylene.

Nominal Diameter: 1.2 mm

Nominal Wall Thickness: 0.3 mm

3.3 LAY UP: 2 Cores laid up.
1. White / Blue
2. Blue**3.4 SCREEN:** Aluminium / Polyester laminate tape in constant contact
with a 7/2 TACW drain wire. Polyester isolation tape between layup
and screen.**3.5 SHEATH:** Coloured 4V75 PVC to AS/NZS3808

Nominal Diameter: 4.20 mm

Nominal Wall Thickness: 0.76 mm

3.6 TYPICAL ELECTRICAL:
TYPICAL CAPACITANCE: 55 pF/m**3.7 PRINTING:** At nominally 1M intervals printed on sheath:**TYCAB AUSTRALIA MULTIPAIR DATA DPF2702 CCL A93/CA/0111****AUSTRALIAN MADE CABLES LEADING THE WAY**