



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833
A.C.N. 100 305 833
269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)
DANDENONG STH VICTORIA 3164
TELEPHONE 03 (Int. 613) 8791 0300
FAX - ADMIN 03 (Int. 613) 9794 0031
CUSTOMER SERVICE
PHONE 03 (Int. 613) 8791 0333
FAX 03 (Int. 613) 9791 8732
www.tycab.com.au

PRODUCT SPECIFICATION

- 1. PRODUCT CODE** DPF4702
- 2. DESCRIPTION** 2 Pair 7/.2 (0.2mmsq) 24AWG. T.A.C.W. Polypropylene insulated.
Aluminium Laminate tape screened. PVC sheathed. Data cable.
- 3. CONSTRUCTION**
- 3.1 CONDUCTOR:** 7 strands of 0.2mm Tinned Annealed Copper to AS/NZS1125 drawn from Class 110A copper to AS/NZS1574.
Max. D.C. resistance at 20C: 89 ohms / km
- 3.2 INSULATION:** Coloured Data Grade Polypropylene.
Nominal Diameter: 1.2 mm
Nominal Wall Thickness: 0.3 mm
- 3.3 LAY UP:** 2 Pairs laid up.
Pair 1. Blue + White / Blue
Pair 2. Orange + White / Orange
- 3.4 SCREEN:** Aluminium / Polyester laminate tape in constant contact with a 7/.2 TACW drain wire.
- 3.4 SHEATH:** Coloured 4V75 PVC to AS/NZS3808
Nominal Diameter: 5.8 mm
Nominal Wall Thickness: 0.76 mm
- 3.5 TYPICAL ELECTRICAL:**
TYPICAL CAPACITANCE: 53 pF/m
TYPICAL IMPEDANCE: 93 ohms
- 3.6 PRINTING:** At nominally 1M intervals printed on sheath:
- TYCAB AUSTRALIA MULTIPAIR DATA DPF4702 CCL A93/CA/0111**

AUSTRALIAN MADE CABLES LEADING THE WAY