



PRODUCT SPECIFICATION

1. PRODUCT CODE DPF6702

2. DESCRIPTION 3 Pair 7/2 (0.2 mm sq) 24AWG .T.A.C.W. Polypropylene insulated.
Aluminium Laminate tape screened. PVC sheathed. Data cable.
NOT FOR MAINS GPO CONNECTION

3. CONSTRUCTION

3.1 CONDUCTOR : 7 strands of 0.2 mm Tinned Annealed Copper to AS1125 drawn from Class 110A copper to AS1574.

Max. D.C. resistance at 20C : 89 ohms / klm

3.2 INSULATION : Coloured Data Grade Polypropylene.

Nominal Diameter : 1.2 mm

Nom. Wall Thickness: 0.3 mm

3.3 LAY UP 3 Pairs laid up.

Pair 1. White/Blue + Blue Pair 2. White/Orange + Orange

Pair 3 White/Green + Green

3.4 SCREEN

Aluminium / Polyester Laminate tape in constant contact with a 7/2 TACW drain wire.

3.4 SHEATH Coloured 4V75 PVC to AS3808 .

Nominal Diameter : 6.2 mm

Nom. Wall Thickness : 0.76 mm

3.5 TYPICAL ELECTRICAL

TYPICAL CAPACITANCE 53 pF/m

TYPICAL IMPEDANCE 93 ohms

3.6 PRINT

At nom 1M intervals

TYCAB AUSTRALIA MULTIPAIR DATA DPF6702 CCL A93/CA/0111