



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833

A.C.N. 100 305 833

269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)

DANDENONG STH VICTORIA 3164

TELEPHONE 03 (Int. 613) 8791 0300

FAX - ADMIN 03 (Int. 613) 9794 0031

CUSTOMER SERVICE

PHONE 03 (Int. 613) 8791 0333

FAX 03 (Int. 613) 97918732

www.tycab.com.au

PRODUCT SPECIFICATION

1. PRODUCT CODE FMC02/1.0

2. DESCRIPTION 2 Core 32/.2 (1.0mm² ,10amp) .P.C.W. V90 PVC insulated.
5V90 P.V.C. sheathed. Flexible supply cord.
250/440 Volt to ASNZS 3191 APPROVAL V98005
Oxygen free copper .RoHS Compliant PVC.

3. CONSTRUCTION

3.1 CONDUCTOR : 32 strands of 0.2 mm nom. Annealed Copper to
AS1125 Class 5
Max. D.C. resistance at 20C : 19.5 ohms / km

3.2 INSULATION : Coloured V90 PVC to AS/NZS 3808.
Nominal Diameter : 2.5 mm
Nom. Wall Thickness: 0.6 mm

3.3 LAY UP 2 Cores laid up .
1. Brown 2. Blue.

3.4 SHEATH Coloured P.V.C. type 5V90 to AS/NZS 3808.
Nominal Diameter : 6.6 mm
Nom. Wall Thickness : 0.8 mm

3.5 IDENTIFICATION

Indented into Sheath at intervals not exceeding 500mm.

TYCAB V90 APP V98005 250/440V ORD DUTY **MM** – metre marked