


PRODUCT SPECIFICATION



- 1. PRODUCT CODE:** FMC250025MM
- 2. DESCRIPTION** 2 Core 50/.25 (2.5mmsq, 20 Amp). Plain Copper Wire.
V90 PVC Insulated & 5V90 P.V.C. Sheathed Flexible cable to AS/NZS 3191.
Approval V94014. 250/440volt ORDINARY DUTY.
Oxygen Free copper.
RoHS compliant P.V.C.
- 3. CONSTRUCTION**
- 3.1 CONDUCTOR:** 50 strands of 0.25 mm nom. Plain Annealed Copper to AS/NZS 1125 drawn from Class 102 copper to AS/NZS 1574.
Max. D.C. resistance at 20C: 8.0 ohms / km
- 3.2 INSULATION:** Coloured V90 P.V.C. to AS/NZS 3808.
Nominal Diameter: 3.6 mm
Nominal Wall Thickness: 0.8 mm
- 3.3 LAY UP:** 2 Cores laid up.
1. Brown
2. Blue
- 3.4 SHEATH:** Coloured P.V.C. type 5V90 to AS/NZS 3808.
Target Diameter: 9.3 mm
Nominal Wall Thickness: 1.0 mm
- 3.5 IDENTIFICATION:** Indented into Sheath at intervals not exceeding 500mm.
TYCAB V90 APP V94014 250/440V ORD DUTY
METRE MARK

