TYCAB AUSTRALIA PTY LTD
A.B.N. 43 100 305 833
A.C.N. 100 305 833
269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)
DANDENONG STH VICTORIA 3164
TELEPHONE 03 (Int. 613) 8791 0300
FAX - ADMIN 03 (Int. 613) 9794 0031
CUSTOMER SERVICE
PHONE 03 (Int. 613) 8791 0333
FAX 03 (Int. 613) 9791 8732
www.tycab.com.au

PRODUCT SPECIFICATION

1. PRODUCT CODE **FMC02/2.5**

2. DESCRIPTION 2 Core 50/.25 (2.5 mm sq ,20amp) .P.C.W. V75 PVC insulated. and 4V75 P.V.C. sheathed. Flexible supply cable to AS3191. Approval V94014 . 250/44volt ORDINARY DUTY . Oxygen free Copper . RoHS compliant PVC .

3. CONSTRUCTION

3.1 CONDUCTOR : 50 strands of 0.25 mm Plain Annealed Copper to AS1125 drawn from Class 102 copper to AS1574. Max. D.C. resistance at 20C : 8.0 ohms / km

3.2 INSULATION : Coloured V75 PVC to AS3808.
Nominal Diameter : 3.6 mm
Nom. Wall Thickness: 0.8 mm

3.3 LAY UP 2 Cores laid up .
1. Brown 2. Blue.

3.4 SHEATH Coloured P.V.C. type 4V75 to AS3808.
Target Diameter : 9.3 mm
Nom. Wall Thickness : 1.0 mm

3.5 IDENTIFICATION
Indented into Sheath at intervals not exceeding 500mm.

"TYCAB V75 APP V94014 250/440V ORD DUTY "

15/9/2010