



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833

A.C.N. 100 305 833

269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)

DANDENONG STH VICTORIA 3164

TELEPHONE 03 (Int. 613) 8791 0300

FAX - ADMIN 03 (Int. 613) 9794 0031

CUSTOMER SERVICE

PHONE 03 (Int. 613) 8791 0333

FAX 03 (Int. 613) 97918732

www.tycab.com.au

PRODUCT SPECIFICATION

1. PRODUCT CODE: FMC03/1.0

2. DESCRIPTION 3 Core 32/.2 (1.0mmsq, 10amp). P.C.W.
V90 PVC insulated & 5V90 P.V.C. sheathed Flexible cord.
250/440 Volt to AS/NZS3191.
Approval ESV130124. Alternative marking V98005
Oxygen Free Copper. RoHS compliant PVC.

3. CONSTRUCTION

3.1 CONDUCTOR: 32 strands of 0.2mm nom. Annealed Copper to AS/NZS1125
drawn from Class 110 copper to AS/NZS1574.

Max. D.C. resistance at 20C: 19.5 ohms / km

3.2 INSULATION: Coloured V90 PVC to AS/NZS 3808.

Nominal Diameter: 2.5 mm

Nominal Wall Thickness: 0.6 mm

3.3 LAY UP: 3 Cores laid up.
1. Brown
2. Light Blue
3. Light Green / Yellow

3.4 SHEATH: Coloured P.V.C. type 5V90 to AS/NZS3808.

Nominal Diameter: 6.9 mm

Nominal Wall Thickness: 0.9 mm

3.5 IDENTIFICATION: **INDENTED** into Sheath at intervals not exceeding 500mm.

TYCAB V90 APP V98005 250/440V ORD DUTY

PRINTED (metre marked)

001M >|<

AUSTRALIAN MADE CABLES LEADING THE WAY