



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833

A.C.N. 100 305 833

269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)

DANDENONG STH VICTORIA 3164

TELEPHONE 03 (Int. 613) 8791 0300

FAX - ADMIN 03 (Int. 613) 9794 0031

CUSTOMER SERVICE

PHONE 03 (Int. 613) 8791 0333

FAX 03 (Int. 613) 97918732

www.tycab.com.au

PRODUCT SPECIFICATION

- 1. PRODUCT CODE** FMC03/4.0
- 2. DESCRIPTION** 3 Core 56/3 (4.0 mm 2) .P.C.W. V90 PVC insulated.
5V90 P.V.C. sheathed. Flexible supply cord.
250/440v to AS/NZS 3191 .ordinary duty .
Oxygen free copper . RoHS compliant PVC
- 3. CONSTRUCTION**
- 3.1 CONDUCTOR :** 56 strands of 0.3 mm Plain Annealed Copper to
AS/NZS 1125 class 5
Max. D.C. resistance at 20C : 5.0 ohms / km
- 3.2 INSULATION :** Coloured V90 PVC to AS/NZS 3808.
Nominal Diameter : 4.1 mm
Nom. Wall Thickness: 0.8 mm
- 3.3 LAY UP** 3 Cores laid up .
1. Brown 2 Lt. Blue 3. Lt Green Yellow
- 3.4 SHEATH** Coloured P.V.C. type 5V90 to AS/NZS 3808.
Nominal Diameter : 11.2 mm
Nom. Wall Thickness : 1.1 mm
- 3.5 IDENTIFICATION** Indented into Sheath at intervals not exceeding 500mm.

TYCAB V90 250/440V ORD DUTY

3.6 PRINTING

Metre marked

AUSTRALIAN MADE CABLES LEADING THE WAY