



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833

A.C.N. 100 305 833

269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)

DANDENONG STH VICTORIA 3164

TELEPHONE 03 (Int. 613) 8791 0300

FAX - ADMIN 03 (Int. 613) 9794 0031

CUSTOMER SERVICE

PHONE 03 (Int. 613) 8791 0333

FAX 03 (Int. 613) 9791 8732

www.tycab.com.au

PRODUCT SPECIFICATION

- 1. PRODUCT CODE** **FMC04/4.0**
- 2. DESCRIPTION** 4 Core 56/.30 (4.0 mm sq ,25amp) .P.C.W. V75 PVC insulated.
4V75 P.V.C. sheathed. Flexible supply cable.
250/440v to AS3191 Ordinary Duty.
Oxygen free Copper . RoHS compliant PVC
- 3. CONSTRUCTION**
- 3.1 CONDUCTOR :** 56 strands of 0.30 mm Plain Annealed Copper to
AS1125 drawn from Class 102 copper to AS1574.
Max. D.C. resistance at 20C : 5.0 ohms / km
- 3.2 INSULATION :** Coloured V75 PVC to AS3808.
Nominal Diameter : 4.15 mm
Nom. Wall Thickness: 0.80 mm
- 3.3 LAY UP** 4 Cores laid up .
1. Brown 2. White 3. Lt Blue 4. Lt Green/Yellow
- 3.4 SHEATH** Coloured P.V.C. type 4V75 to AS3808.
Nominal Diameter : 12.9 mm
Nom. Wall Thickness : 1.1 mm
- 3.5 IDENTIFICATION** Indented into Sheath at intervals not exceeding 500mm.

“TYCAB 75c “