



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833

A.C.N. 100 305 833

269 FRANKSTON-DANDENONG ROAD

(LOCKED BAG 1413)

DANDENONG STH VICTORIA 3164

TELEPHONE 03 (Int. 613) 8791 0300

FAX - ADMIN 03 (Int. 613) 9794 0031

CUSTOMER SERVICE

PHONE 03 (Int. 613) 8791 0333

FAX 03 (Int. 613) 9791 8732

www.tycab.com.au

PRODUCT SPECIFICATION

- 1. PRODUCT CODE** **FMC05/0.75**
- 2. DESCRIPTION** 5 Core 24/.20 (.75 mm sq ,7.5amp) .P.C.W. V75 PVC insulated.
4V75 P.V.C. sheathed. Flexible cord.
250/440 Volt to AS3191 . Ordinary duty .
- 3. CONSTRUCTION**
- 3.1 CONDUCTOR :** 24 strands of 0.2 mm nom. Annealed Copper to
AS1125 drawn from Class 102 copper to AS1574.
Max. D.C. resistance at 20C : 26.07 ohms / km
- 3.2 INSULATION :** Coloured V75 PVC to AS3808.
Nominal Diameter : 2.3 mm
Nom. Wall Thickness: 0.6 mm
- 3.3 LAY UP** 5 Cores laid up .
1. Lt Blue 2. Brown 3 .White
4. Orange 5..Green / Yellow
- 3.4 SHEATH** Coloured P.V.C. type 4V75 to AS3808.
Nominal Diameter : 8.1 mm
Nom. Wall Thickness : 0.9 mm
- 3.5 IDENTIFICATION** Indented into Sheath at intervals not exceeding 500mm.

“TYCAB V75 250/440V ORD DUTY “