



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833

A.C.N. 100 305 833

269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)

DANDENONG STH VICTORIA 3164

TELEPHONE 03 (Int. 613) 8791 0300

FAX - ADMIN 03 (Int. 613) 9794 0031

CUSTOMER SERVICE

PHONE 03 (Int. 613) 8791 0333

FAX 03 (Int. 613) 97918732

www.tycab.com.au

PRODUCT SPECIFICATION

- 1. PRODUCT CODE:** FMC05/1.0
- 2. DESCRIPTION** 5 Core 32/.2 (1.0mmsq, 10amp). P.C.W.
V90 PVC insulated & 5V90 P.V.C. sheathed Flexible cord.
250/440 Volt to AS/NZS 3191 Ordinary Duty.
Oxygen Free Copper. RoHS compliant PVC.
- 3. CONSTRUCTION**
- 3.1 CONDUCTOR:** 32 strands of 0.2mm nom. Annealed Copper to AS/NZS 1125
drawn from Class 110A copper to AS/NZS 1574.
Max. D.C. resistance at 20C: 19.5 ohms / km
- 3.2 INSULATION:** Coloured V90 PVC to AS/NZS 3808.
Nominal Diameter: 2.5 mm
Nominal Wall Thickness: 0.6mm
- 3.3 LAY UP:** 5 Cores laid up.
1. Light Blue 2. Brown
3. White 4. Black
5. Green / Yellow
- 3.4 SHEATH:** Coloured P.V.C. type 5V90 to AS/NZS 3808.
Nominal Diameter: 8.5 mm
Nominal Wall Thickness: 0.9mm
- 3.5 IDENTIFICATION:** **INDENTED** into Sheath at intervals not exceeding 500mm.

TYCAB V90 250/440V ORD DUTY

PRINTED (metre marked)

001M >|<

AUSTRALIAN MADE CABLES LEADING THE WAY