TYCAB AUSTRALIA PTY LTD
A.B.N. 43 100 305 833
A.C.N. 100 305 833
269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)
DANDENONG STH VICTORIA 3164
TELEPHONE 03 (Int. 613) 8791 0300
FAX - ADMIN 03 (Int. 613) 9794 0031
CUSTOMER SERVICE
PHONE 03 (Int. 613) 8791 0333
FAX 03 (Int. 613) 9791 8732
www.tycab.com.au

PRODUCT SPECIFICATION

1. PRODUCT CODE **FMC05/1.5**

2. DESCRIPTION 5 Core 30/.25 (1.5 mm sq ,15amp) .P.C.W. V75 PVC insulated.
4V75 P.V.C. sheathed. Flexible cord.
250/440 Volt to AS3191 . Ordinary Duty.

3. CONSTRUCTION

3.1 CONDUCTOR : 30 strands of 0.25 mm Annealed Copper to AS1125 drawn from Class 102 copper to AS1574.
Max. D.C. resistance at 20C : 13.3 ohms / km

3.2 INSULATION : Coloured V75 PVC to AS3808.
Nominal Diameter : 2.95 mm
Nom. Wall Thickness: 0.7 mm

3.3 LAY UP 5 Cores laid up .
1. Lt Blue 2. Brown 3.White
4. Orange 5..Green / Yellow

3.4 SHEATH Coloured P.V.C. type 4V75 to AS3808.
Nominal Diameter : 10.3 mm
Nom. Wall Thickness : 1.1 mm

3.5 IDENTIFICATION
Indented into Sheath at intervals not exceeding 500mm.

"TYCAB 75c "