



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833

A.C.N. 100 305 833

269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)

DANDENONG STH VICTORIA 3164

TELEPHONE 03 (Int. 613) 8791 0300

FAX - ADMIN 03 (Int. 613) 9794 0031

CUSTOMER SERVICE

PHONE 03 (Int. 613) 8791 0333

FAX 03 (Int. 613) 97918732

www.tycab.com.au

PRODUCT SPECIFICATION

- 1. PRODUCT CODE** **FMC12/0.75**
- 2. DESCRIPTION** 12 Core 24/.2 (0.75 mm sq ,7.5amp) .P.C.W. V90 PVC insulated.
5V90 P.V.C. sheathed. Flexible supply cord.
Generally to AS/NZS 3191 250/440 Volt.
- 3. CONSTRUCTION**
- 3.1 CONDUCTOR :** 24 strands of 0.2 mm nom. Annealed Copper to
AS1125 Class 5. Max. D.C. resistance at 20C : 26.0 ohms / km
- 3.2 INSULATION :** Coloured V90 PVC to AS/NZS 3191.
Nominal Diameter : 2.3 mm
Nom. Wall Thickness: 0.6 mm
- 3.3 LAY UP** 12 Cores laid up .
1 . Black 2 . Red 3 . Lt Blue 4 . Orange
5 . Grey 6 . Violet 7 . Pink 8 . White
9 . Yellow 10 . Green 11 . Brown 12 . Brown/White
- 3.4 SHEATH** Coloured P.V.C. type 5V90 to AS/NZS 3191.
Nominal Diameter : 11.7 mm
Nom. Wall Thickness : 0.9 mm
- 3.5 IDENTIFICATION** Indented into Sheath at intervals not exceeding 500mm.