



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833
A.C.N. 100 305 833
269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)
DANDENONG STH VICTORIA 3164
TELEPHONE 03 (Int. 613) 8791 0300
FAX - ADMIN 03 (Int. 613) 9794 0031
CUSTOMER SERVICE
PHONE 03 (Int. 613) 8791 0333
FAX 03 (Int. 613) 9791 8732
www.tycab.com.au

PRODUCT SPECIFICATION

1. PRODUCT CODE: FRL21602

2. DESCRIPTION 2 Core 16/0.2 (0.5mmsq, 4.0amp). P.C.W.
V90 PVC insulated & 5V90 P.V.C. sheathed Flexible cable.
To AS/NZS3191 Light Duty 250/250 Volt
Oxygen Free Copper. RoHS compliant PVC.

3. CONSTRUCTION

3.1 CONDUCTOR: 16 strands of 0.2mm nom. Annealed Copper to AS/NZS1125 drawn from Class 102 copper to AS/NZS1574.

Max. D.C. resistance at 20C: 39.0 ohms / km

3.2 INSULATION: Coloured V90 PVC to AS/NZS3808.

Nominal Diameter: 2.0 mm
Nominal Wall Thickness: 0.5 mm

3.3 LAY UP: 2 Cores laid up.
1. Brown
2. Blue

3.4 SHEATH: Coloured P.V.C. type 5V90 to AS/NZS3808.

Nominal Diameter: 5.3 mm
Nominal Wall Thickness: 0.6 mm

3.5 IDENTIFICATION: Printed in contrasting colour on the Sheath at intervals not exceeding 500mm.

TYCAB V90 APP V98005 250/250V LIGHT DUTY

AUSTRALIAN MADE CABLES LEADING THE WAY