



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833
A.C.N. 100 305 833
269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)
DANDENONG STH VICTORIA 3164
TELEPHONE 03 (Int. 613) 8791 0300
FAX - ADMIN 03 (Int. 613) 9794 0031
CUSTOMER SERVICE
PHONE 03 (Int. 613) 8791 0333
FAX 03 (Int. 613) 9791 8732
www.tycab.com.au

PRODUCT SPECIFICATION



1. PRODUCT CODE **FVK12402**

2. DESCRIPTION **24/2 (0.75mmsq) Tinned Annealed Copper
V90HT PVC insulated, 0.6/1kv rated to AS/NZS3191.
Oxygen Free copper. RoHS Compliant.**

3.1 CONDUCTOR: 24 strands of 0.2mm nom. Tinned Annealed Copper to
AS/NZS1125, drawn from Class 102 copper to AS/NZS1574.

Max. D.C. resistance at 20C: 26.7 ohms / km

3.2 INSULATION: Coloured P.V.C. type V90HT to AS/NZS3808
(Formerly V105)

Nominal Diameter: 2.80 mm

Nominal Wall Thickness: 0.76 mm

3.3 IDENTIFICATION: Indented into the insulation at max. 200mm:

TYCAB HT90 0.6/1KV