

TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833
A.C.N. 100 305 833
269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)
DANDENONG STH VICTORIA 3164
TELEPHONE 03 (Int. 613) 8791 0300
FAX - ADMIN 03 (Int. 613) 9794 0031
CUSTOMER SERVICE
PHONE 03 (Int. 613) 8791 0333
FAX 03 (Int. 613) 9791 8732
www.tycab.com.au

PRODUCT SPECIFICATION



1. PRODUCT CODE FVK150025

2. DESCRIPTION 50/.25 (2.5mmsq) Tinned Annealed Copper

V90HT PVC insulated, 0.6/1kv to AS/NZS3191. Oxygen Free copper. RoHS compliant PVC.

3.1 CONDUCTOR: 50 strands of 0.25 mm nom. Tinned Annealed Copper to

AS/NZS1125, drawn from Class 102 copper to AS/NZS1574.

Max. D.C. resistance at 20C: 8.2 ohms / km

3.2 INSULATION: Coloured P.V.C. type V90HT to AS/NZS3808

(Formerly V105)

Nominal Diameter: 3.95 mm
Nominal Wall Thickness: 0.9 mm
Minimum at any point: 0.71 mm

3.3 IDENTIFICATION: Indented into the insulation at max. 200mm:

"TYCAB HT90 0.6/1KV"

3.4 EARTH STRIPE: Green with Yellow extruded stripe, the stripe surface coverage

greater than 30% and less than 70% coverage, as per AS/NZS3191.

Applied as a dual stripe.