




TYCAB NEW ZEALAND

Tycab NZ Ltd
6A Donnor Place
Mt Wellington 1061
Auckland
Email: info@tycab.co.nz
Call: 0800 888 636

PRODUCT SPECIFICATION



1. PRODUCT CODE HFXT25203

2. DESCRIPTION 2 X 52/.3 (4mmsq). Tinned Copper Wire, XLPE Insulated & XLPE Sheathed in Twin format.
To PV1-F specification. TUV 2pfG 1169
1.8Kv dc -40c to 120c

3. CONSTRUCTION

3.1 CONDUCTOR: 52 strands of 0.3mm nom. TINNED Annealed Copper to AS/NZS 1125 Class 5

Max. D.C. resistance at 20C: 5.09 ohms / km

3.2 INSULATION: XLPE

Nominal Wall Thickness: 0.60 mm

3.3 CORE COLOURS: 1. Black
2. Red

3.4 SHEATH: BLACK with RED polarity stripe on side of Red core
XLPE Single Double Insulated (TWIN)
configuration

Nominal Dimensions: 5.5 x 11.4 mm

Nominal Wall Thickness: 0.6 mm

3.5 IDENTIFICATION: Printed on sheath in contrasting colour –

HFXT2520- PV1-F TUV 2pfG 1169 2 x 4MM2 0.9/1.8kV DC UV STABLE DC USE ONLY - DO NOT DISCONNECT UNDER LOAD - 001M >I<