



## TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833  
A.C.N. 100 305 833  
269 FRANKSTON-DANDENONG ROAD  
(LOCKED BAG 1413)  
DANDENONG STH VICTORIA 3164  
TELEPHONE 03 (Int. 613) 8791 0300  
FAX - ADMIN 03 (Int. 613) 9794 0031  
CUSTOMER SERVICE  
PHONE 03 (Int. 613) 8791 0333  
FAX 03 (Int. 613) 9791 8732  
[www.tycab.com.au](http://www.tycab.com.au)

## PRODUCT SPECIFICATION

- 1. PRODUCT CODE** HML31602
- 2. DESCRIPTION** 3 Core 16/2 (0.5mmsq, 4.0amp)  
P.C.W. V75 PVC insulated. 4V75 P.V.C. sheathed Flexible cable.  
**Dimensionally** to AS3191 250/250volt Light Duty construction only.  
Not an Approved item.  
Not for Mains Connection.
- 3. CONSTRUCTION**
- 3.1 CONDUCTORS:** 16 strands of 0.20 mm Annealed Copper to AS1125 drawn from Class 110A copper to AS1574.  
Max. D.C. resistance at 20C : 39.0 ohms / km
- 3.2 INSULATION:** Coloured V75 PVC to AS3191.  
Nominal Diameter: 2.0 mm  
Nominal Wall Thickness: 0.5 mm
- 3.3 LAY UP** 3 cores laid up.  
1. Brown  
2. Blue.  
3. Light Green / Yellow
- 3.4 SHEATH** Coloured P.V.C. type 4V75 to AS3191.  
Nominal Diameter: 5.6 mm  
Nominal Wall Thickness: 0.6 mm
- 3.5 IDENTIFICATION** Indented into Sheath at intervals not exceeding 500mm.  
"TYCAB V75"