



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833
A.C.N. 100 305 833
269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)
DANDENONG STH VICTORIA 3164
TELEPHONE 03 (Int. 613) 8791 0300
FAX - ADMIN 03 (Int. 613) 9794 0031
CUSTOMER SERVICE
PHONE 03 (Int. 613) 8791 0333
FAX 03 (Int. 613) 9791 8732
www.tycab.com.au

PRODUCT SPECIFICATION

- 1. PRODUCT CODE:** HRM21602MM
- 2. DESCRIPTION** 2 Core 16/.2 (0.5mmsq, 4.0amp). P.C.W.
V90 PVC insulated & 5V90 P.V.C. sheathed Flexible cable.
Dimensions to AS/NZS 3191 Ordinary Duty 250/440volt.
Oxygen Free Copper. RoHS compliant PVC.

3. CONSTRUCTION

- 3.1 CONDUCTOR:** 16 strands of 0.2mm nom. Annealed Copper to AS/NZS 1125 drawn from Class 102 copper to AS/NZS 1574.
Max. D.C. resistance at 20C: 39.0 ohms / km
- 3.2 INSULATION:** Coloured V90 PVC to AS/NZS 3808.
Nominal Diameter: 2.2 mm
Nominal Wall Thickness: 0.6 mm
- 3.3 LAY UP:** 2 Cores laid up.
1. Brown
2. Blue
- 3.4 SHEATH:** Coloured P.V.C. type 5V90 to AS/NZS 3808.
Nominal Diameter: 6.0 mm
Nominal Wall Thickness: 0.8 mm
- 3.5 IDENTIFICATION:** **INDENTED** into Sheath at intervals not exceeding 500mm.

TYCAB V90 250/440V ORD DUTY

And print metre marked

TYCAB AUSTRALIA	
CUSTOMER AUTHORISATION	
SIGNED:	DATE:

AUSTRALIAN MADE CABLES LEADING THE WAY