



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833

A.C.N. 100 305 833

269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)

DANDENONG STH VICTORIA 3164

TELEPHONE 03 (Int. 613) 8791 0300

FAX - ADMIN 03 (Int. 613) 9794 0031

CUSTOMER SERVICE

PHONE 03 (Int. 613) 8791 0333

FAX 03 (Int. 613) 9791 8732

www.tycab.com.au

PRODUCT SPECIFICATION



1. PRODUCT CODE LEC2142

2. DESCRIPTION **2 Core Parallel Webbed (Figure 8) 14/.2 (0.4mmsq). P.A.C.W.
V75 P.V.C insulated. Extra Low Voltage. Not for mains connection.
Oxygen Free Copper. RoHS compliant PVC.**

3. CONSTRUCTION

3.1 CONDUCTOR: 14 strands of 0.2mm nom. Plain Annealed Copper to
AS/NZS 1125 drawn from Class 102 copper to AS/NZS 1574.

Max. D.C. resistance at 20C: 45 ohms / km

3.2 INSULATION: Coloured 75C P.V.C. to AS/NZS 3808.
Parallel Webbed (Figure 8) construction

Nominal Diameter: 1.6 x 3.3 mm

Nominal Wall Thickness: 0.36 mm

3.3 IDENTIFICATION: Polarity ribs on one leg.

Printed: **RACOL SECURITY LEC2142 ACA N1155**