



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833
A.C.N. 100 305 833
269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)
DANDENONG STH VICTORIA 3164
TELEPHONE 03 (Int. 613) 8791 0300
FAX - ADMIN 03 (Int. 613) 9794 0031
CUSTOMER SERVICE
PHONE 03 (Int. 613) 8791 0333
FAX 03 (Int. 613) 9791 8732
www.tycab.com.au

PRODUCT SPECIFICATION



- 1. PRODUCT CODE** LFC21402
- 2. DESCRIPTION** 2 Core Parallel Webbed (Figure 8) 14/.2 (0.4mmsq). P.A.C.W.
V75 P.V.C insulated.
Extra Low Voltage. Not for mains GPO connection.
Oxygen Free copper. RoHS compliant PVC.
- 3. CONSTRUCTION**
- 3.1 CONDUCTOR:** 14 strands of 0.2mm Plain Annealed Copper to
AS/NZS 1125 drawn from Class 102 copper to AS/NZS 1574.
Max. D.C. resistance at 20C: 44.8 ohms / km
- 3.2 INSULATION:** Coloured V75 P.V.C. to AS/NZS 3808.
Parallel Webbed (Figure 8) construction
Nominal Diameter: 1.75 x 3.8 mm
Nominal Wall Thickness: 0.4 mm
- 3.3 IDENTIFICATION:** Polarity ribs on one leg.
- 3.4 BRANDED:** TYCAB LFC21402 AUSTEL APP