



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833

A.C.N. 100 305 833

269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)

DANDENONG STH VICTORIA 3164

TELEPHONE 03 (Int. 613) 8791 0300

FAX - ADMIN 03 (Int. 613) 9794 0031

CUSTOMER SERVICE

PHONE 03 (Int. 613) 8791 0333

FAX 03 (Int. 613) 9791 8732

www.tycab.com.au

PRODUCT SPECIFICATION



1. PRODUCT CODE LFD212702

2. DESCRIPTION 2 Core Parallel Webbed (Figure 8) 127/.2 (4.0mmsq). P.A.C.W.
FLEXIBLE U.V resistant P.V.C insulated.
Low Voltage cable. Not for mains connection.

3. CONSTRUCTION

3.1 CONDUCTOR: 127 strands of 0.2mm Plain Annealed Copper to AS/NZS1125
drawn from Class 110A copper to AS/NZS1574.

Max. D.C. resistance at 20C: 4.63 ohms / km

3.2 INSULATION: Coloured U.V Resistant P.V.C.
Parallel Webbed (Figure 8 configuration).

Nominal Diameter: 4.70 x 9.5 mm

Nominal Wall Thickness: 1.0 mm

3.3 POLARITY IDENTIFICATION: By permanent raised rib on one leg.

METRE MARK LOW NUMBER ON BOTTOM HIGH NUMBER ON TOP

AUSTRALIAN MADE CABLES LEADING THE WAY