



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833
A.C.N. 100 305 833
269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)
DANDENONG STH VICTORIA 3164
TELEPHONE 03 (Int. 613) 8791 0300
FAX - ADMIN 03 (Int. 613) 9794 0031
CUSTOMER SERVICE
PHONE 03 (Int. 613) 8791 0333
FAX 03 (Int. 613) 9791 8732
www.tycab.com.au

PRODUCT SPECIFICATION



1. PRODUCT CODE LFD219202

2. DESCRIPTION 2 Core Parallel Webbed (Figure 8) 192/.2 (6.0mmsq). P.A.C.W.
FLEXIBLE U.V resistant P.V.C insulated.
Low Voltage cable. Not for mains connection.

3. CONSTRUCTION

3.1 CONDUCTOR: 192 strands of 0.2mm Plain Annealed Copper to AS/NZS1125
drawn from Class 110A copper to AS/NZS1574.

Max. D.C. resistance at 20C: 3.1 ohms / km

3.2 INSULATION: Coloured U.V Resistant P.V.C.
Parallel Webbed (Figure 8 configuration).

Nominal Diameter: 5.5 x 11.5 mm
Nominal Wall Thickness: 1.0 mm

3.3 POLARITY IDENTIFICATION: By 4 permanent raised ribs on one leg.

METRE MARK LOW NUMBER ON BOTTOM HIGH NUMBER ON TOP

AUSTRALIAN MADE CABLES LEADING THE WAY