



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833

A.C.N. 100 305 833

269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)

DANDENONG STH VICTORIA 3164

TELEPHONE 03 (Int. 613) 8791 0300

FAX - ADMIN 03 (Int. 613) 9794 0031

CUSTOMER SERVICE

PHONE 03 (Int. 613) 8791 0333

FAX 03 (Int. 613) 9791 8732

www.tycab.com.au

PRODUCT SPECIFICATION

1. PRODUCT CODE LFD230025

2. DESCRIPTION 2 Core Parallel Webbed (Figure 8) 30/.25 (1.5 mm sq). P.A.C.W.
FLEXIBLE U.V resistant V90HT P.V.C insulated.
Extra Low Voltage Garden Light cable. Not for mains connection.
Oxygen Free copper. RoHS compliant PVC.

3. CONSTRUCTION

3.1 CONDUCTOR: 30 strands of 0.25mm Plain Annealed Copper to AS/NZS 1125
drawn from Class 102 copper to AS/NZS 1574.

Max. D.C. resistance at 20C: 13.7 ohms / km

3.2 INSULATION: Coloured U.V Resistant V90HT P.V.C. to AS/NZS 3808
Parallel Webbed (Figure 8 configuration).

Nominal Diameter: 4.0 x 8.3 mm

Nominal Wall Thickness: 1.1 mm

3.3 POLARITY IDENTIFICATION: By permanent raised rib on one leg.

3.4 PRINTING: TYCAB GARDEN LIGHTING 1.5MMSQ 001M >|<

METRE MARK LOW NUMBER ON BOTTOM HIGH NUMBER ON TOP

AUSTRALIAN MADE CABLES LEADING THE WAY