



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833

A.C.N. 100 305 833

269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)

DANDENONG STH VICTORIA 3164

TELEPHONE 03 (Int. 613) 8791 0300

FAX - ADMIN 03 (Int. 613) 9794 0031

CUSTOMER SERVICE

PHONE 03 (Int. 613) 8791 0333

FAX 03 (Int. 613) 9791 8732

www.tycab.com.au

PRODUCT SPECIFICATION

1.PRODUCT CODE **LFX219202**

2. DESCRIPTION 2 Core Parallel Webbed (Figure 8)192/.2 (6.00 mm sq) .P.A.C.W.
FLEXIBLE , CLEAR P.V.C insulated . Extra Low Voltage cable.
Not for mains outlet connection.

3. CONSTRUCTION

3.1 CONDUCTOR : 192 strands of 0.2 mm Plain Annealed Copper to
AS1125 drawn from Class 110A copper to AS1574.
Max. D.C. resistance at 20C : 3.1 ohms / klm

3.2 INSULATION : CLEAR P.V.C...
Parallel Webbed (figure 8 configuration)..
Nominal Diameter : 5.50 x 11.5mm
Nom. Wall Thickness: 1.00 mm

3.4 POLARITY IDENTIFICATION

By STRIPE on one leg of the figure 8 :