



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833
A.C.N. 100 305 833
269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)
DANDENONG STH VICTORIA 3164
TELEPHONE 03 (Int. 613) 8791 0300
FAX - ADMIN 03 (Int. 613) 9794 0031
CUSTOMER SERVICE
PHONE 03 (Int. 613) 8791 0333
FAX 03 (Int. 613) 9791 8732
www.tycab.com.au

PRODUCT SPECIFICATION

- 1. PRODUCT CODE:** LFX26502
- 2. DESCRIPTION:** 2 Core Parallel Webbed (Figure 8) 65/.2 (2.0mmsq). P.A.C.W.
FLEXIBLE CLEAR P.V.C insulated. Extra Low Voltage cable.
Not for mains connection.
Oxygen Free copper. RoHS compliant PVC.
- 3. CONSTRUCTION**
- 3.1 CONDUCTOR:** 65 strands of 0.2mm nom. Plain Annealed Copper to AS1125 drawn from Class 102 copper to AS1574.
Max. D.C. resistance at 20C : 9.1 ohms / km
- 3.2 INSULATION:** CLEAR P.V.C. 75c min. rating.
Parallel Webbed (Figure 8 configuration)
- Nominal Diameter: 3.35 x 7.20mm
Nominal Wall Thickness: 0.66 mm
- 3.3 POLARITY IDENTIFICATION:**
By STRIPE on one leg as per customer order.
- 3.4 PRINTING:** On sheath at 1M intervals (metre marked):
- TYCAB 2mm² 2x65/.2 Speaker Cable 001M >|<**