



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833

A.C.N. 100 305 833

269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)

DANDENONG STH VICTORIA 3164

TELEPHONE 03 (Int. 613) 8791 0300

FAX - ADMIN 03 (Int. 613) 9794 0031

CUSTOMER SERVICE

PHONE 03 (Int. 613) 8791 0333

FAX 03 (Int. 613) 9791 8732

www.tycab.com.au

PRODUCT SPECIFICATION

1.PRODUCT CODE LFX28402

2. DESCRIPTION 2 Core Parallel Webbed (Figure 8) 84/.2 (2.6 mm sq) .P.A.C.W.
CLEAR P.V.C insulated. Extra Low Voltage .
Extra Low Voltage . Not for mains outlet connection.
Oxygen free copper . RoHS compliant PVC .

3. CONSTRUCTION

3.1 CONDUCTOR : 84 strands of 0.2 mm nom. Plain Annealed Copper to
AS1125 drawn from Class 102 copper to
AS1574.
Max. D.C. resistance at 20C : 7.1 ohms / km

3.2 INSULATION : CLEAR P.V.C...75c min. rating.
Parallel Webbed (figure 8)..construction

Nominal Diameter : 4.25 x 9.0 mm

Nom. Wall Thickness: 1.0 mm

3.3 IDENTIFICATION :
Polarity by coloured stripe on one leg as per customer order .