



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833

A.C.N. 100 305 833

269 FRANKSTON-DANDENONG ROAD

(LOCKED BAG 1413)

DANDENONG STH VICTORIA 3164

TELEPHONE 03 (Int. 613) 8791 0300

FAX - ADMIN 03 (Int. 613) 9794 0031

CUSTOMER SERVICE

PHONE 03 (Int. 613) 8791 0333

FAX 03 (Int. 613) 9791 8732

www.tycab.com.au

PRODUCT SPECIFICATION

1.PRODUCT CODE **MET2CK025**

2. DESCRIPTION 2 x 30/.25 (1.5 mm sq) .T.A.C.W. V90HT insulated
0.6/1kv unprotected Single Cores
held together in a thin pvc sheath.
Not for Mains GPO Connection.

3. CONSTRUCTION

3.1 CONDUCTOR : 30 strands of 0.25 mm Tinned Annealed Copper to
AS1125 drawn from Class 110A copper to
AS1574. Max. D.C. resistance at 20C : 13.7 ohms / klm

3.2 INSULATION : Coloured V90HT P.V.C. to AS3808.

Nominal Diameter : 3.15 mm

Nom. Wall Thickness: 0.8 mm

3.3 CORE COLOURS

1. Red 2. Black

Laid parallel.

3.4 SHEATH : Coloured V90HT to AS3808
Flat configuration

Nominal Dimensions : 4.1 x 7.3 mm

Nom. Wall Thickness : 0.46 mm