



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833

A.C.N. 100 305 833

269 FRANKSTON-DANDENONG ROAD

(LOCKED BAG 1413)

DANDENONG STH VICTORIA 3164

TELEPHONE 03 (Int. 613) 8791 0300

FAX - ADMIN 03 (Int. 613) 9794 0031

CUSTOMER SERVICE

PHONE 03 (Int. 613) 8791 0333

FAX 03 (Int. 613) 9791 8732

www.tycab.com.au

PRODUCT SPECIFICATION

1.PRODUCT CODE MTT53202

2. DESCRIPTION 5 Core 32/.2 (1.0 sqmm) .TINNED V90 PVC insulated.
5V90 sheathed marine trailer cable.
60 Volt DC or 25 Volt AC . Not for Mains connection.

3. CONSTRUCTION

3.1 CONDUCTOR : 32 strands of 0.2mm TINNED Annealed Copper to AS1125 drawn from Class 110A copper to AS1574.
Max. D.C. resistance at 20C : 20 ohms / klm

3.2 INSULATION : Coloured V90 PVC to AS3808.
Nominal Diameter : 2.2 mm
Nom. Wall Thickness: 0.4 mm

3.3 LAY UP 5 Cores laid up .
1. White 2. Yellow 3. Brown 4. Red 5. Green

3.4 SHEATH Coloured P.V.C. type 5V90 to AS3808.
Nominal Diameter : 7.2 mm
Nom. Wall Thickness : 0.6 mm

3.5 FINISH Solid fill round sheath

3.6 IDENTIFICATION

PRINTED on sheath

TYCAB MARINE TRAILER CABLE 5 x 1.0mmsq

And metre marked