




TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833
A.C.N. 100 305 833
269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)
DANDENONG STH VICTORIA 3164
TELEPHONE 03 (Int. 613) 8791 0300
FAX - ADMIN 03 (Int. 613) 9794 0031
CUSTOMER SERVICE
PHONE 03 (Int. 613) 8791 0333
FAX 03 (Int. 613) 9791 8732
www.tycab.com.au

PRODUCT SPECIFICATION



- 1. PRODUCT CODE** SEC6142
- 2. DESCRIPTION:** **6 Core 14 / .2 (0.4mmsq) V75 insulated, V75C PVC sheathed. Austel Approval CCL A95/CA/0153.**
Security Cable. Extra Low Voltage use.
Not for mains connection.
Oxygen Free Copper. RoHS Compliant PVC.
- 3. CONSTRUCTION**
- 3.1 CONDUCTOR:** 14 strands of 0.2 mm nom. Annealed Copper to AS/NZS 1125 drawn from Class 102 copper to AS/NZS 1574.
Max. D.C. resistance at 20C: 44.8 ohms / km
- 3.2 INSULATION:** Coloured P.V.C to AS/NZS 3808 type V75.
Nominal Diameter: 1.5 mm
Nominal Wall Thickness: 0.3 mm
- 3.3 LAY UP:** 6 cores twisted.
1. Black 2. White
3. Red 4. Blue
5. Green 6. Yellow
- 3.4 SHEATH:** Coloured P.V.C. to AS/NZS 3808 type V75
Nominal Diameter: 5.5 mm
Nominal Wall Thickness: 0.5 mm
Note: Finish is typically **ROPY**.
- 3.5 PRINTING:** Printed on the sheath
“RACOL SECURITY SEC6142 CCL A95/CA/0153”
at maximum 1000mm spacing.

AUSTRALIAN MADE CABLES LEADING THE WAY