TYCAB NZ LIMITED
6A Donnor Place
Mt Wellington
P.O. Box 132 247
Sylvia Park, Auckland 1644
Tel. 09 573 1990
www.tycab.co.nz

PRODUCT SPECIFICATION

1. PRODUCT CODE **SET472**

2. DESCRIPTION:
4 Core 7/0.2 TCW
V75 insulated & V75 PVC sheathed.
Security Cable. Extra Low Voltage.
Not for mains connection.
Oxygen Free Copper. RoHS Compliant PVC.

3. CONSTRUCTION

3.1 CONDUCTOR: 7 strands of 0.2 mm nom. Tinned Annealed Copper to AS/NZS1125

drawn from Class 102 copper to AS/NZS1574.

Max. D.C. resistance at 20C: 89.5 ohms / km

3.2 INSULATION: Coloured P.V.C to AS/NZS3808 type V75.

Nominal Diameter: 1.15 mm
Nominal Wall Thickness: 0.26 mm

3.3 LAY UP: 4 cores twisted
1. Black
2. White
3. Red
4. Blue

3.4 SHEATH: Coloured P.V.C. to AS/NZS3808 type 4V75

Nominal Diameter: 3.9 mm
Nominal Wall Thickness: 0.5 mm

Note: Finish is typically **ROPY**

3.5 PRINTING: **"Tycab NZ SECURITY SET472"**

at maximum 1000mm spacing.