



PRODUCT SPECIFICATION

1. PRODUCT CODE: SET6142

2. DESCRIPTION: **6 core 14/2 (0.44 mmsq) TCW V75 insulated, V75 PVC sheathed.**
Security Cable. Extra low voltage use.
Not for mains connection.
Oxygen Free Copper. RoHS Compliant PVC.

3. CONSTRUCTION

3.1 CONDUCTOR : 14 strands of 0.2 mm nom. TINNED Annealed Copper to AS/NZS1125 drawn from Class 110A copper to AS/NZS1574.
Max. D.C. resistance at 20C : 44.8 ohms / klm

3.2 INSULATION : Coloured P.V.C to AS/NZS3808 type V75.

Nominal Diameter : 1.50 mm
Nom. Wall Thickness: 0.30 mm

3.3 LAY UP : 6 cores twisted.
1.Black 2.White 3.Red 4. Blue 5.Green 6. Yellow

3.4 SHEATH : Coloured P.V.C. to AS/NZS3808 type V75

Nominal Diameter : 5.5 mm
Nom. Wall Thickness : 0.50 mm

Note : Finish is typically **ROPY**.

3.5 PRINTING : Printed on Sheath

TYCAB SECURITY SET6142 CCL A95/CA/0153
At maximum 1000mm spacing.