



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833
A.C.N. 100 305 833
269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)
DANDENONG STH VICTORIA 3164
TELEPHONE 03 (Int. 613) 8791 0300
FAX - ADMIN 03 (Int. 613) 9794 0031
CUSTOMER SERVICE
PHONE 03 (Int. 613) 8791 0333
FAX 03 (Int. 613) 9791 8732
www.tycab.com.au

PRODUCT SPECIFICATION

- 1. PRODUCT CODE:** SMC81402
- 2. DESCRIPTION:** 8 core 14/.2 PCW (0.4mmsq)
V75 insulated & V75 PVC sheathed.
Security Cable. Extra Low Voltage.
Not for mains connection.
Oxygen Free Copper. RoHS Compliant PVC.
- 3. CONSTRUCTION**
- 3.1 CONDUCTOR:** 14 strands of 0.2 mm nom. Annealed Copper to AS/NZS1125
drawn from Class 102 copper to AS/NZS1574.
Max. D.C. resistance at 20C: 44.8 ohms / km
- 3.2 INSULATION:** Coloured P.V.C to AS/NZS3808 type V75.
Nominal Diameter: 1.5 mm
Nominal Wall Thickness: 0.3 mm
- 3.3 LAY UP:** 8 cores twisted.
1. Red
2. Blue
3. White
4. Black
5. Green
6. Yellow
7. Brown
8. Violet
- 3.4 SHEATH:** Coloured P.V.C. to AS/NZS3808 type 4V75
Nominal Diameter: 6.5 mm
Nominal Wall Thickness: 0.76 mm
Note: Finish is typically **ROPY**
- 3.5 PRINTING:** on sheath:
TYCAB AUSTRALIA SECURITY SMC81402 CCL A93/CA/0071

AUSTRALIAN MADE CABLES LEADING THE WAY