

PRODUCT SPECIFICATION

1. PRODUCT CODE: **SMT81402**

2. DESCRIPTION: 8 core 14/.2 TCW (0.4mmsq)
V75 insulated & V75 PVC sheathed.
Security Cable. Extra Low Voltage.
Not for mains connection.
Oxygen Free Copper. RoHS Compliant PVC.

3. CONSTRUCTION

3.1 CONDUCTOR: 14 strands of 0.2 mm nom. Tinned Annealed Copper to
AS/NZS1125
drawn from Class 102 copper to AS/NZS1574.

Max. D.C. resistance at 20C: 44.8 ohms / km

3.2 INSULATION: Coloured P.V.C to AS/NZS3808 type V75.

Nominal Diameter: 1.5 mm
Nominal Wall Thickness: 0.3 mm

3.3 LAY UP: 8 cores twisted.
1. Red
2. Blue
3. White
4. Black
5. Green
6. Yellow
7. Brown
8. Violet

3.4 SHEATH: Coloured P.V.C. to AS/NZS3808 type 4V75

Nominal Diameter: 6.5 mm
Nominal Wall Thickness: 0.76 mm

Note: Finish is typically **ROPY**

3.5 PRINTING: on sheath:

TYCAB NZ SECURITY SMT81402